

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
1/15**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1 Product identifier

Product name: Chlorine
Trade name: Chlorine 2.8 Chemical, Chlorine 4.0, Chlorine 5.0

Additional identification

Chemical name: Chlorine
Chemical formula: Cl₂
INDEX No. 017-001-00-7
CAS-No. 7782-50-5
EC No. 231-959-5
REACH Registration No. 01-2119486560-35

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional. Perform risk assessment prior to use.
Bleaching agent.
Use as an Intermediate (transported, on-site isolated).
Use for electronic component manufacture.
Use of gas to manufacture pharmaceutical products.
Using gas alone or in mixtures for the calibration of analysis equipment.
Using gas as feedstock in chemical processes.
Using gas for metal treatment.
Water treatment.
Formulation of mixtures with gas in pressure receptacles.
Biocidal uses.
Uses advised against Consumer use.

1.3 Details of the supplier of the safety data sheet

Supplier

AGA SIA
Katrinas iela 5
LV-1045 Riga Latvia

Telephone: + 371 80005005

E-mail: info@lv.aga.com

1.4 Emergency telephone number: Saindēšanās un zāļu informācijas centrs, tel. +371 6704 2473

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Oxidizing gases	Category 1	H270: May cause or intensify fire; oxidizer.
Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
2/15

Health Hazards

Acute toxicity (Inhalation - gas)	Category 2	H330: Fatal if inhaled.
Skin irritation	Category 2	H315: Causes skin irritation.
Serious eye irritation	Category 2	H319: Causes serious eye irritation.
Specific Target Organ Toxicity - Single Exposure	Category 3	H335: May cause respiratory irritation.

Environmental Hazards

Acute hazards to the aquatic environment	Category 1	H400: Very toxic to aquatic life.
Chronic hazards to the aquatic environment	Category 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label Elements

Contains: Chlorine



Signal Words: Danger

Hazard Statement(s): H270: May cause or intensify fire; oxidizer.
H280: Contains gas under pressure; may explode if heated.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H330: Fatal if inhaled.
H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention: P220: Keep/Store away from combustible materials.
P244: Keep valves and fittings free from oil and grease.
P260: Do not breathe gas/vapors.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response: P302+P352: IF ON SKIN: Wash with plenty of water.
P332+P313: If skin irritation occurs: Get medical advice/attention.
P304+P340+P315: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice/attention.
P305+P351+P338+P315: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
P370+P376: In case of fire: Stop leak if safe to do so.

Storage: P403: Store in a well-ventilated place.
P405: Store locked up.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
3/15

Disposal: None.

Supplemental label information

EUH071: Corrosive to the respiratory tract.

2.3 Other hazards: Contact with evaporating liquid may cause frostbite or freezing of skin.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name	Chlorine
INDEX No.:	017-001-00-7
CAS-No.:	7782-50-5
EC No.:	231-959-5
REACH Registration No.:	01-2119486560-35
Purity:	100%
	The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name:	Chlorine 2.8 Chemical, Chlorine 4.0, Chlorine 5.0

SECTION 4: First aid measures

General: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Contact with evaporating liquid may cause frostbite or freezing of skin.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Irritating to eyes, respiratory system and skin. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Irritating to eyes, respiratory system and skin. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. May be fatal if inhaled.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
4/15

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention. Treat with a corticosteroid spray as soon as possible after inhalation.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Use water spray to reduce vapors or divert vapor cloud drift. Water Spray or Fog. Dry powder. Foam. Carbon Dioxide.

Unsuitable extinguishing media: None.

5.2 Special hazards arising from the substance or mixture: Fire or excessive heat may produce hazardous decomposition products. Supports combustion.

5.3 Advice for firefighters

Special fire fighting procedures: In case of fire: Stop leak if safe to do so. Use of water may result in the formation of very toxic aqueous solutions. Keep run-off water out of sewers and water sources. Dike for water control. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.

Special protective equipment for fire-fighters: Gas tight chemically protective clothing (Type 1) in combination with self contained breathing apparatus.
Guideline: EN 943-2 Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Performance requirements for gas-tight (Type 1) chemical protective suits for emergency teams (ET)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: Evacuate area. Eliminate all ignition sources if safe to do so. Provide adequate ventilation. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

6.2 Environmental Precautions: Prevent further leakage or spillage if safe to do so. Reduce vapour with fog or fine water spray. Keep run-off water out of sewers and water sources. Dike for water control.

6.3 Methods and material for containment and cleaning up: Provide adequate ventilation. Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4 Reference to other sections: Refer to sections 8 and 13.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
5/15

SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling:** Only experienced and properly instructed persons should handle gases under pressure. Avoid exposure - obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Keep equipment free from oil and grease. Open valve slowly to avoid pressure shock. Use only oxygen approved lubricants and sealants. Use only with equipment cleaned for oxygen service and rated for the pressure. Installation of a cross purge assembly between the container and the regulator is recommended. Excess pressure must be vented through an appropriate scrubber system. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.
- 7.2 Conditions for safe storage, including any incompatibilities:** Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material. Avoid asphalted locations for storage, transfer and use (ignition risk if spilt). Segregate from flammable gases and other flammable materials being stored.
- 7.3 Specific end use(s):** None.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
6/15

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	type	Exposure Limit Values	Source
Chlorine	STEL	0,5 ppm 1,5 mg/m ³	EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU (12 2009)
	TWA	0,3 ppm 1 mg/m ³	Latvia. OELs. Occupational exposure limit values of chemical substances in work environment (02 2011)
	STEL	0,5 ppm 1,5 mg/m ³	Latvia. OELs. Occupational exposure limit values of chemical substances in work environment (02 2011)

DNEL-Values

Critical component	type	Value	Remarks
Chlorine	Worker - inhalative, long-term - systemic	0,75 mg/m ³	-
	Worker - inhalative, short-term - systemic	1,5 mg/m ³	-
	Worker - inhalative, long-term - local	0,75 mg/m ³	-
	Worker - inhalative, short-term - local	1,5 mg/m ³	-
	Worker - dermal, long-term - local	0,5 % wt	-

PNEC-Values

Critical component	type	Value	Remarks
Chlorine	Aquatic (freshwater)	0,21 µg/l	-
	Sewage treatment plant	0,03 mg/l	-
	Aquatic (intermit. releases)	0,26 µg/l	-
	Aquatic (marine water)	0,042 µg/l	-

8.2 Exposure controls

Appropriate engineering controls:

Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below occupational exposure limits. Gas detectors should be used when toxic quantities may be released. Gas detectors should be used when quantities of oxidizing gases may be released. Avoid oxygen rich (>23,5%) atmospheres. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system and under strictly controlled conditions. Only use permanent leak tight installations (e.g. welded pipes). Do not eat, drink or smoke when using the product.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
7/15

Individual protection measures, such as personal protective equipment

- General information:** A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Keep suitable chemically resistant protective clothing readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Protect eyes, face and skin from contact with product. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.
- Eye/face protection:** Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases. Guideline: EN 166 Personal Eye Protection.
- Skin protection**
- Hand Protection:** Wear working gloves while handling containers
Guideline: EN 388 Protective gloves against mechanical risks.
Chemically resistant gloves complying with EN 374 should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Guideline: EN 374-1/2/3 Protective gloves against chemicals and micro-organisms.
For short term use:
Material: Chloroprene rubber.
Break-through time: > 30 min
Glove thickness: 0,4 mm
For long term use:
Material: Fluoroelastomer.
Break-through time: > 480 min
Glove thickness: 0,7 mm
- Body protection:** No special precautions.
- Other:** Wear safety shoes while handling containers
Guideline: ISO 20345 Personal protective equipment - Safety footwear.
- Respiratory Protection:** Reference should be made to European Standard EN 689 for methods for the assessment of exposure by inhalation to chemical agents and national guidance documents for methods for the determination of hazardous substances. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.
Material: Filter B
Guideline: EN 14387 Respiratory protective devices. Gas filter(s) and combined filter(s). Requirements, testing, marking.
Guideline: EN 136 Respiratory protective devices. Full face masks. Requirements, testing, marking.
- Thermal hazards:** No precautionary measures are necessary.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
8/15

Hygiene measures: Obtain special instructions before use. Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.

Environmental exposure controls: For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Liquefied gas
Color:	Greenish yellow
Odor:	Pungent irritating odor.
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
pH:	If dissolved in water pH-value will be affected.
Melting Point:	-101 °C
Boiling Point:	-34 °C
Sublimation Point:	not applicable.
Critical Temp. (°C):	144,0 °C
Flash Point:	Not applicable to gases and gas mixtures.
Evaporation Rate:	Not applicable to gases and gas mixtures.
Flammability (solid, gas):	Nonflammable Gas, but a strong oxidizer
Flammability Limit - Upper (%):	not applicable.
Flammability Limit - Lower (%):	not applicable.
Vapor pressure:	6.780 hPa (20 °C) Experimental result, Key study
Vapor density (air=1):	2,5
Relative density:	No data available.
Solubility(ies)	
Solubility in Water:	5,1 g/l (30 °C)
Partition coefficient (n-octanol/water):	Not known.
Autoignition Temperature:	not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,346 mPa.s (20 °C) Liquid 0,013 mPa.s (20 °C) Gas
Explosive properties:	Not applicable.
Oxidizing properties:	Oxidizing

9.2 Other information: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
9/15

Molecular weight: 70,91 g/mol (Cl₂)

SECTION 10: Stability and reactivity

- 10.1 Reactivity:** No reactivity hazard other than the effects described in sub-section below.
- 10.2 Chemical Stability:** Stable under normal conditions.
- 10.3 Possibility of hazardous reactions:** Violently oxidises organic material. May react violently with combustible materials. May react violently with reducing agents.
- 10.4 Conditions to avoid:** Avoid moisture in the installation.
- 10.5 Incompatible Materials:** Moisture. Combustible materials Reducing agents. Keep equipment free from oil and grease. For material compatibility see latest version of ISO-11114. Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (>30 bar) oxygen lines and equipment in case of combustion.
- 10.6 Hazardous Decomposition Products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on toxicological effects

**Acute toxicity - Oral
Product**

Based on available data, the classification criteria are not met.

Chlorine

LD 50 (Rat): 8.910 mg/kg Remarks: Read-across from supporting substance (structural analogue or surrogate), Supporting study

**Acute toxicity - Dermal
Product**

Based on available data, the classification criteria are not met.

Chlorine

LD 50 (Rabbit): > 20.000 mg/kg Remarks: Read-across from supporting substance (structural analogue or surrogate), Key study

**Acute toxicity - Inhalation
Product**

Fatal if inhaled.

Chlorine

LC 50 (Rat, 1 h): 293 ppm
LC 50 (Rat, 4 h): 146,5 ppm Remarks: Delayed fatal pulmonary oedema possible.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
10/15**Skin Corrosion/Irritation****Product** Causes skin irritation.

Chlorine Severely irritating to skin.

Serious Eye Damage/Eye Irritation**Product** Causes serious eye irritation.

Chlorine Severely irritating to eyes.

Respiratory or Skin Sensitization**Product** Based on available data, the classification criteria are not met.**Germ Cell Mutagenicity****Product** Based on available data, the classification criteria are not met.**Carcinogenicity****Product** Based on available data, the classification criteria are not met.**Reproductive toxicity****Product** Based on available data, the classification criteria are not met.**Specific Target Organ Toxicity - Single Exposure****Product** May cause respiratory irritation.Chlorine Route of Exposure: Inhalation - vapor
Severe corrosion to the respiratory tract at high concentrations.**Specific Target Organ Toxicity - Repeated Exposure****Product** Based on available data, the classification criteria are not met.**Aspiration Hazard****Product** Not applicable to gases and gas mixtures..**SECTION 12: Ecological information****General information:** Avoid release to the environment. Product is not allowed to be discharged into ground water or the aquatic environment.**12.1 Toxicity****Acute toxicity****Product** Very toxic to aquatic life with long lasting effects.**Acute toxicity - Fish**

Chlorine LC 50 (Oncorhynchus mykiss, 96 h): 0,17 mg/l (Static) Remarks: Read-across from supporting substance (structural analogue or surrogate), Supporting study

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
11/15

LC 50 (Fish, 96 h): 0,032 mg/l

Acute toxicity - Aquatic Invertebrates

Chlorine LC 50 (Water flea (*Daphnia magna*), 48 h): 0,15 mg/l (Static) Remarks: Mortality
LC 50 (*Brachionus calyciflorus*, 24 h): 0,37 mg/l (Static) Remarks: Read-across from supporting substance (structural analogue or surrogate), Supporting study

Toxicity to microorganisms

Chlorine EC 50 (Algae (*Scenedesmus subspicatus*), 72 h): 0,001 mg/l

Chronic Toxicity - Aquatic Invertebrates

Chlorine NOAEL (*V. iris* (*Ambloplites rupestris*) and *Cottus carolinae* (*E. capsaeformis*), 21 d): 10 µg/l (flow-through) Read-across from supporting substance (structural analogue or surrogate), Supporting study

Additional ecological information

None.

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures..

Biodegradation

Inorganic The product is not readily biodegradable.

12.3 Bioaccumulative potential

Product The substance has no potential for bioaccumulation.

12.4 Mobility in soil

Product The substance has low mobility in soil.

12.5 Results of PBT and vPvB

assessment
Product Not classified as PBT or vPvB.

12.6 Other adverse effects:

Other Ecological Information

May cause pH changes in aqueous ecological systems. Depending on local conditions and existing concentrations, disturbances in the biodegradation process of activated sludge are possible.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Must not be discharged to atmosphere. Consult supplier for specific recommendations.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
12/15

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org>) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container: 16 05 04*: Gases in pressure containers (including halons) containing dangerous substances.

SECTION 14: Transport information**ADR**

14.1 UN Number: UN 1017
14.2 UN Proper Shipping Name: CHLORINE
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.3, 5.1, 8
Hazard No. (ADR): 265
Tunnel restriction code: (C/D)
14.4 Packing Group: -
14.5 Environmental hazards: Environmentally Hazardous
14.6 Special precautions for user: -

RID

14.1 UN Number: UN 1017
14.2 UN Proper Shipping Name: CHLORINE
14.3 Transport Hazard Class(es)
Class: 2
Label(s): 2.3, 5.1, 8
14.4 Packing Group: -
14.5 Environmental hazards: Environmentally Hazardous
14.6 Special precautions for user: -

IMDG

14.1 UN Number: UN 1017
14.2 UN Proper Shipping Name: CHLORINE
14.3 Transport Hazard Class(es)
Class: 2.3
Label(s): 2.3, 5.1, 8
EmS No.: F-C, S-U
14.3 Packing Group: -
14.5 Environmental hazards: Marine Pollutant
14.6 Special precautions for user: -

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
13/15

IATA

14.1 UN Number: UN 1017
 14.2 Proper Shipping Name: Chlorine
 14.3 Transport Hazard Class(es):
 Class: 2.3
 Label(s): -
 14.4 Packing Group: -
 14.5 Environmental hazards: Environmentally Hazardous
 14.6 Special precautions for user: -
 Other information
 Passenger and cargo aircraft: Forbidden.
 Cargo aircraft only: Forbidden.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: not applicable

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Directive 96/61/EC: concerning integrated pollution prevention and control (IPPC): Article 15, European Pollution Emission Registry (EPER):

Chemical name	CAS-No.	Concentration
Chlorine	7782-50-5	100%

Directive 96/82/EC (Seveso III): on the control of major accident hazards involving dangerous substances:

Chemical name	CAS-No.	Concentration
Chlorine	7782-50-5	100%

Directive 98/24/EC on the protection of workers from the risks related to chemical agents at work:

Chemical name	CAS-No.	Concentration
Chlorine	7782-50-5	100%

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
14/15

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 89/686/EEC on personal protective equipment Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.

This Safety Data Sheet has been produced to comply with Regulation (EU) 2015/830.

15.2 Chemical safety assessment: CSA has been carried out.

SECTION 16: Other information

Revision Information: Not relevant.

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:

- Agency for Toxic Substances and Diseases Registry (ATSDR) (<http://www.atsdr.cdc.gov/>).
- European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
- European Chemical Agency: Information on Registered Substances <http://apps.echa.europa.eu/registered/registered-sub.aspx#search>
- European Industrial Gases Association (EIGA) Doc. 169 Classification and Labelling guide.
- International Programme on Chemical Safety (<http://www.inchem.org/>)
- ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
- Matheson Gas Data Book, 7th Edition.
- National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
- The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (<http://ecb.jrc.ec.europa.eu/esis/>).
- The European Chemical Industry Council (CEFIC) ERICards.
- United States of America's National Library of Medicine's toxicology data network TOXNET (<http://toxnet.nlm.nih.gov/index.html>)
- Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
- Substance specific information from suppliers.
- Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H270	May cause or intensify fire; oxidizer.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

Chlorine

Issue Date: 16.01.2013
Last revised date: 22.08.2017

Version: 1.0

SDS No.: 000010021781
15/15

Training information: Users of breathing apparatus must be trained. Ensure operators understand the toxicity hazard. Ensure operators understand the hazards.

Classification according to Regulation (EC) No 1272/2008 as amended.

Ox. Gas 1, H270
Press. Gas Liq. Gas, H280
Acute Tox. 2, H330
Skin Irrit. 2, H315
Eye Irrit. 2, H319
STOT SE 3, H335
Aquatic Acute 1, H400
Aquatic Chronic 1, H410

Other information: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date: 22.08.2017

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.